

Package ‘reticulate’

January 14, 2022

Type Package

Title Interface to 'Python'

Version 1.23

Description Interface to 'Python' modules, classes, and functions. When calling into 'Python', R data types are automatically converted to their equivalent 'Python' types. When values are returned from 'Python' to R they are converted back to R types. Compatible with all versions of 'Python' ≥ 2.7 .

License Apache License 2.0

URL <https://rstudio.github.io/reticulate/>,
<https://github.com/rstudio/reticulate>

BugReports <https://github.com/rstudio/reticulate/issues>

SystemRequirements Python ($\geq 2.7.0$)

Encoding UTF-8

Depends R (≥ 3.0)

Imports Matrix, Rcpp ($\geq 0.12.7$), RcppTOML, graphics, here, jsonlite, methods, png, rappdirs, utils, withr

Suggests callr, knitr, rlang, rmarkdown, testthat

LinkingTo Rcpp

RoxygenNote 7.1.2

VignetteBuilder knitr

NeedsCompilation yes

Author Kevin Ushey [aut, cre],
JJ Allaire [aut],
RStudio [cph, fnd],
Yuan Tang [aut, cph] (<<https://orcid.org/0000-0001-5243-233X>>),
Dirk Eddelbuettel [ctb, cph],
Bryan Lewis [ctb, cph],
Sigrid Keydana [ctb],
Ryan Hafen [ctb, cph],
Marcus Geelnard [ctb, cph] (TinyThread library,
<http://tinythreadpp.bitsnbites.eu/>)

Maintainer Kevin Ushey <kevin@rstudio.com>

Repository CRAN

Date/Publication 2022-01-14 21:12:47 UTC

R topics documented:

array_reshape	3
as.character.python.builtin.bytes	4
conda-tools	5
configure_environment	7
dict	8
eng_python	9
import	10
install_miniconda	11
install_python	12
iterate	13
miniconda_path	14
miniconda_uninstall	14
miniconda_update	14
np_array	15
py	15
PyClass	16
py_available	16
py_bool	17
py_capture_output	18
py_config	18
py_del_attr	19
py_del_item	19
py_discover_config	20
py_ellipsis	20
py_eval	21
py_exe	22
py_func	22
py_function_custom_scaffold	23
py_get_attr	24
py_get_item	25
py_has_attr	25
py_help	26
py_id	26
py_install	27
py_is_null_xptr	28
py_iterator	29
py_last_error	30
py_len	30
py_list_attributes	31
py_list_packages	32
py_main_thread_func	33

py_module_available	33
py_none	34
py_run	34
py_save_object	35
py_set_attr	35
py_set_item	36
py_set_seed	36
py_str	37
py_suppress_warnings	37
py_unicode	38
py_version	38
r-py-conversion	39
repl_python	39
source_python	41
tuple	42
use_python	42
virtualenv-tools	44
with.python.builtin.object	46

Index 47

array_reshape	<i>Reshape an Array</i>
---------------	-------------------------

Description

Reshape (reindex) a multi-dimensional array, using row-major (C-style) reshaping semantics by default.

Usage

```
array_reshape(x, dim, order = c("C", "F"))
```

Arguments

x	An array
dim	The new dimensions to be set on the array.
order	The order in which elements of x should be read during the rearrangement. "C" means elements should be read in row-major order, with the last index changing fastest; "F" means elements should be read in column-major order, with the first index changing fastest.

Details

This function differs from e.g. `dim(x) <- dim` in a very important way: by default, `array_reshape()` will fill the new dimensions in row-major (C-style) ordering, while `dim<-()` will fill new dimensions in column-major (Fortran-style) ordering. This is done to be consistent with libraries like NumPy, Keras, and TensorFlow, which default to this sort of ordering when reshaping arrays. See the examples for why this difference may be important.

Examples

```
## Not run:
# let's construct a 2x2 array from a vector of 4 elements
x <- 1:4

# rearrange will fill the array row-wise
array_reshape(x, c(2, 2))
#      [,1] [,2]
# [1,]  1  2
# [2,]  3  4
# setting the dimensions 'fills' the array col-wise
dim(x) <- c(2, 2)
x
#      [,1] [,2]
# [1,]  1  3
# [2,]  2  4

## End(Not run)
```

as.character.python.builtin.bytes

Convert Python bytes to an R character vector

Description

Convert Python bytes to an R character vector

Usage

```
## S3 method for class 'python.builtin.bytes'
as.character(x, encoding = "utf-8", errors = "strict", ...)
```

Arguments

x	object to be coerced or tested.
encoding	Encoding to use for conversion (defaults to utf-8)
errors	Policy for handling conversion errors. Default is 'strict' which raises an error. Other possible values are 'ignore' and 'replace'.
...	further arguments passed to or from other methods.

`conda-tools`*Conda Tools*

Description

Tools for managing Python conda environments.

Usage

```
conda_list(conda = "auto")

conda_create(
  envname = NULL,
  packages = NULL,
  ...,
  forge = TRUE,
  channel = character(),
  environment = NULL,
  conda = "auto",
  python_version = miniconda_python_version()
)

conda_clone(envname, ..., clone = "base", conda = "auto")

conda_export(
  envname,
  file = if (json) "environment.json" else "environment.yml",
  json = FALSE,
  ...,
  conda = "auto"
)

conda_remove(envname, packages = NULL, conda = "auto")

conda_install(
  envname = NULL,
  packages,
  forge = TRUE,
  channel = character(),
  pip = FALSE,
  pip_options = character(),
  pip_ignore_installed = FALSE,
  conda = "auto",
  python_version = NULL,
  ...
)
```

```
conda_binary(conda = "auto")
conda_exe(conda = "auto")
conda_version(conda = "auto")
conda_update(conda = "auto")
conda_python(envname = NULL, conda = "auto", all = FALSE)
```

Arguments

conda	The path to a conda executable. Use "auto" to allow <code>reticulate</code> to automatically find an appropriate conda binary. See Finding Conda and <code>conda_binary()</code> for more details.
envname	The name of, or path to, a conda environment.
packages	A character vector, indicating package names which should be installed or removed. Use <code>python=<version></code> to request the installation of a specific version of Python.
...	Optional arguments, reserved for future expansion.
forge	Boolean; include the <code>conda-forge</code> repository?
channel	An optional character vector of conda channels to include. When specified, the <code>forge</code> argument is ignored. If you need to specify multiple channels, including the conda forge, you can use <code>c("conda-forge", <other channels>)</code> .
environment	The path to an environment definition, generated via (for example) <code>conda_export()</code> , or via <code>conda env export</code> . When provided, the conda environment will be created using this environment definition, and other arguments will be ignored.
python_version	The version of Python to be installed. Set this if you'd like to change the version of Python associated with a particular conda environment.
clone	The name of the conda environment to be cloned.
file	The path where the conda environment definition will be written.
json	Boolean; should the environment definition be written as JSON? By default, conda exports environments as YAML.
pip	Boolean; use pip for package installation? By default, packages are installed from the active conda channels.
pip_options	An optional character vector of additional command line arguments to be passed to pip. Only relevant when <code>pip = TRUE</code> .
pip_ignore_installed	Ignore already-installed versions when using pip? (defaults to FALSE). Set this to TRUE so that specific package versions can be installed even if they are downgrades. The FALSE option is useful for situations where you don't want a pip install to attempt an overwrite of a conda binary package (e.g. SciPy on Windows which is very difficult to install via pip due to compilation requirements).
all	Boolean; report all instances of Python found?

Value

`conda_list()` returns an R data frame, with `name` giving the name of the associated environment, and `python` giving the path to the Python binary associated with that environment.

`conda_create()` returns the path to the Python binary associated with the newly-created conda environment.

`conda_clone()` returns the path to Python within the newly-created conda environment.

`conda_export()` returns the path to the exported environment definition, invisibly.

Finding Conda

Most of `reticulate`'s conda APIs accept a `conda` parameter, used to control the conda binary used in their operation. When `conda = "auto"`, `reticulate` will attempt to automatically find a conda installation. The following locations are searched, in order:

1. The location specified by the `reticulate.conda_binary` R option,
2. The location specified by the `RETICULATE_CONDA` environment variable,
3. The `miniconda_path()` location (if it exists),
4. The program `PATH`,
5. A set of pre-defined locations where conda is typically installed.

To force `reticulate` to use a particular conda binary, we recommend setting:

```
options(reticulate.conda_binary = "/path/to/conda")
```

This can be useful if your conda installation lives in a location that `reticulate` is unable to automatically discover.

`configure_environment` *Configure a Python Environment*

Description

Configure a Python environment, satisfying the Python dependencies of any loaded R packages.

Usage

```
configure_environment(package = NULL, force = FALSE)
```

Arguments

- | | |
|----------------------|--|
| <code>package</code> | The name of a package to configure. When <code>NULL</code> , <code>reticulate</code> will instead look at all loaded packages and discover their associated Python requirements. |
| <code>force</code> | Boolean; force configuration of the Python environment? Note that <code>configure_environment()</code> is a no-op within non-interactive R sessions. Use this if you require automatic environment configuration, e.g. when testing a package on a continuous integration service. |

Details

Normally, this function should only be used by package authors, who want to ensure that their package dependencies are installed in the active Python environment. For example:

```
.onLoad <- function(libname, pkgname) {
  reticulate::configure_environment(pkgname)
}
```

If the Python session has not yet been initialized, or if the user is not using the default Miniconda Python installation, no action will be taken. Otherwise, `reticulate` will take this as a signal to install any required Python dependencies into the user's Python environment.

If you'd like to disable `reticulate`'s auto-configure behavior altogether, you can set the environment variable:

```
RETICULATE_AUTOCONFIGURE = FALSE
```

e.g. in your `~/.Renviron` or similar.

Note that, in the case where the Python session has not yet been initialized, `reticulate` will automatically ensure your required Python dependencies are installed after the Python session is initialized (when appropriate).

dict

Create Python dictionary

Description

Create a Python dictionary object, including a dictionary whose keys are other Python objects rather than character vectors.

Usage

```
dict(..., convert = FALSE)
```

```
py_dict(keys, values, convert = FALSE)
```

Arguments

<code>...</code>	Name/value pairs for dictionary (or a single named list to be converted to a dictionary).
<code>convert</code>	TRUE to automatically convert Python objects to their R equivalent. If you pass FALSE you can do manual conversion using the <code>py_to_r()</code> function.
<code>keys</code>	Keys to dictionary (can be Python objects)
<code>values</code>	Values for dictionary

Value

A Python dictionary

Note

The returned dictionary will not automatically convert its elements from Python to R. You can do manual conversion with the `py_to_r()` function or pass `convert = TRUE` to request automatic conversion.

eng_python

A reticulate Engine for Knitr

Description

This provides a reticulate engine for knitr, suitable for usage when attempting to render Python chunks. Using this engine allows for shared state between Python chunks in a document – that is, variables defined by one Python chunk can be used by later Python chunks.

Usage

```
eng_python(options)
```

Arguments

options Chunk options, as provided by knitr during chunk execution.

Details

The engine can be activated by setting (for example)

```
knitr::knit_engines$set(python = reticulate::eng_python)
```

Typically, this will be set within a document's setup chunk, or by the environment requesting that Python chunks be processed by this engine. Note that knitr (since version 1.18) will use the reticulate engine by default when executing Python chunks within an R Markdown document.

import	<i>Import a Python module</i>
--------	-------------------------------

Description

Import the specified Python module, making it available for use from R.

Usage

```
import(module, as = NULL, convert = TRUE, delay_load = FALSE)
```

```
import_main(convert = TRUE)
```

```
import_builtins(convert = TRUE)
```

```
import_from_path(module, path = ".", convert = TRUE, delay_load = FALSE)
```

Arguments

module	The name of the Python module.
as	An alias for module name (affects names of R classes). Note that this is an advanced parameter that should generally only be used in package development (since it affects the S3 name of the imported class and can therefore interfere with S3 method dispatching).
convert	Boolean; should Python objects be automatically converted to their R equivalent? If set to FALSE, you can still manually convert Python objects to R via the py_to_r() function.
delay_load	Boolean; delay loading the module until it is first used? When FALSE, the module will be loaded immediately. See Delay Load for advanced usages.
path	The path from which the module should be imported.

Value

An R object wrapping a Python module. Module attributes can be accessed via the \$ operator, or via [py_get_attr\(\)](#).

Python Built-ins

Python's built-in functions (e.g. `len()`) can be accessed via Python's built-in module. Because the name of this module has changed between Python 2 and Python 3, we provide the function `import_builtins()` to abstract over that name change.

Delay Load

The `delay_load` parameter accepts a variety of inputs. If you just need to ensure your module is lazy-loaded (e.g. because you are a package author and want to avoid initializing Python before the user has explicitly requested it), then passing `TRUE` is normally the right choice.

You can also provide a list of named functions, which act as callbacks to be run when the module is later loaded. For example:

```
delay_load = list(  
  
  # run before the module is loaded  
  before_load = function() { ... }  
  
  # run immediately after the module is loaded  
  on_load = function() { ... }  
  
  # run if an error occurs during module import  
  on_error = function(error) { ... }  
  
)
```

Alternatively, if you supply only a single function, that will be treated as an `on_load` handler.

Import from Path

`import_from_path()` can be used if you need to import a module from an arbitrary filesystem path. This is most commonly used when importing modules bundled with an R package – for example:

```
path <- system.file("python", package = <package>)  
reticulate::import_from_path(<module>, path = path, delay_load = TRUE)
```

Examples

```
## Not run:  
main <- import_main()  
sys <- import("sys")  
  
## End(Not run)
```

install_miniconda *Install Miniconda*

Description

Download the [Miniconda](#) installer, and use it to install Miniconda.

Usage

```
install_miniconda(path = miniconda_path(), update = TRUE, force = FALSE)
```

Arguments

path	The location where Miniconda is (or should be) installed. Note that the Miniconda installer does not support paths containing spaces. See miniconda_path for more details on the default path used by reticulate.
update	Boolean; update to the latest version of Miniconda after installation?
force	Boolean; force re-installation if Miniconda is already installed at the requested path?

Details

For arm64 builds of R on macOS, `install_miniconda()` will use binaries from [miniforge](#) instead.

Note

If you encounter binary incompatibilities between R and Miniconda, a scripted build and installation of Python from sources can be performed by [install_python\(\)](#)

See Also

Other miniconda-tools: [miniconda_uninstall\(\)](#), [miniconda_update\(\)](#)

install_python

Install Python

Description

Download and install Python, using the [pyenv](#). and [pyenv-win](#) projects.

Usage

```
install_python(version, list = FALSE, force = FALSE)
```

Arguments

version	The version of Python to install.
list	Boolean; if set, list the set of available Python versions?
force	Boolean; force re-installation even if the requested version of Python is already installed?

Details

In general, it is recommended that Python virtual environments are created using the copies of Python installed by `install_python()`. For example:

```
library(reticulate)
version <- "3.8.7"
install_python(version = version)
virtualenv_create("my-environment", python_version = version)
use_virtualenv("my-environment")
```

iterate	<i>Traverse a Python iterator or generator</i>
---------	--

Description

Traverse a Python iterator or generator

Usage

```
iterate(it, f = base::identity, simplify = TRUE)
```

```
iter_next(it, completed = NULL)
```

```
as_iterator(x)
```

Arguments

it	Python iterator or generator
f	Function to apply to each item. By default applies the <code>identity</code> function which just reflects back the value of the item.
simplify	Should the result be simplified to a vector if possible?
completed	Sentinel value to return from <code>iter_next()</code> if the iteration completes (defaults to <code>NULL</code> but can be any R value you specify).
x	Python iterator or iterable

Details

Simplification is only attempted all elements are length 1 vectors of type "character", "complex", "double", "integer", or "logical".

Value

For `iterate()`, A list or vector containing the results of calling `f` on each item in `x` (invisibly);
 For `iter_next()`, the next value in the iteration (or the sentinel `completed` value if the iteration is complete).

miniconda_path	<i>Path to Miniconda</i>
----------------	--------------------------

Description

The path to the Miniconda installation to use. By default, an OS-specific path is used. If you'd like to instead set your own path, you can set the RETICULATE_MINICONDA_PATH environment variable.

Usage

```
miniconda_path()
```

miniconda_uninstall	<i>Remove Miniconda</i>
---------------------	-------------------------

Description

Uninstall Miniconda.

Usage

```
miniconda_uninstall(path = miniconda_path())
```

Arguments

path	The path in which Miniconda is installed.
------	---

See Also

Other miniconda-tools: [install_miniconda\(\)](#), [miniconda_update\(\)](#)

miniconda_update	<i>Update Miniconda</i>
------------------	-------------------------

Description

Update Miniconda to the latest version.

Usage

```
miniconda_update(path = miniconda_path())
```

Arguments

path The location where Miniconda is (or should be) installed. Note that the Miniconda installer does not support paths containing spaces. See [miniconda_path](#) for more details on the default path used by reticulate.

See Also

Other miniconda-tools: [install_miniconda\(\)](#), [miniconda_uninstall\(\)](#)

np_array *NumPy array*

Description

Create NumPy arrays and convert the data type and in-memory ordering of existing NumPy arrays.

Usage

```
np_array(data, dtype = NULL, order = "C")
```

Arguments

data Vector or existing NumPy array providing data for the array
dtype Numpy data type (e.g. "float32", "float64", etc.)
order Memory ordering for array. "C" means C order, "F" means Fortran order.

Value

A NumPy array object.

py *Interact with the Python Main Module*

Description

The py object provides a means for interacting with the Python main session directly from R. Python objects accessed through py are automatically converted into R objects, and can be used with any other R functions as needed.

Usage

```
py
```

Format

An R object acting as an interface to the Python main module.

PyClass

Create a python class

Description

Create a python class

Usage

```
PyClass(classname, defs = list(), inherit = NULL)
```

Arguments

classname	Name of the class. The class name is useful for S3 method dispatch.
defs	A named list of class definitions - functions, attributes, etc.
inherit	A list of Python class objects. Usually these objects have the <code>python.builtin.type</code> S3 class.

Examples

```
## Not run:
Hi <- PyClass("Hi", list(
  name = NULL,
  `__init__` = function(self, name) {
    self$name <- name
    NULL
  },
  say_hi = function(self) {
    paste0("Hi ", self$name)
  }
))

a <- Hi("World")

## End(Not run)
```

py_available*Check if Python is available on this system*

Description

Check if Python is available on this system

Usage

```
py_available(initialize = FALSE)
```

```
py_numpy_available(initialize = FALSE)
```

Arguments

`initialize` TRUE to attempt to initialize Python bindings if they aren't yet available (defaults to FALSE).

Value

Logical indicating whether Python is initialized.

Note

The `py_numpy_available` function is a superset of the `py_available` function (it calls `py_available` first before checking for NumPy).

py_bool

Python Truthiness

Description

Equivalent to `bool(x)` in Python, or `not not x`.

Usage

```
py_bool(x)
```

Arguments

`x`, A python object.

Details

If the Python object defines a `__bool__` method, then that is invoked. Otherwise, if the object defines a `__len__` method, then TRUE is returned if the length is nonzero. If neither `__len__` nor `__bool__` are defined, then the Python object is considered TRUE. If `x`

Value

An R scalar logical: TRUE or FALSE. If `x` is a null pointer or Python is not initialized, FALSE is returned.

py_capture_output	<i>Capture and return Python output</i>
-------------------	---

Description

Capture and return Python output

Usage

```
py_capture_output(expr, type = c("stdout", "stderr"))
```

Arguments

expr	Expression to capture stdout for
type	Streams to capture (defaults to both stdout and stderr)

Value

Character vector with output

py_config	<i>Python configuration</i>
-----------	-----------------------------

Description

Retrieve information about the version of Python currently being used by reticulate.

Usage

```
py_config()
```

Details

If Python has not yet been initialized, then calling `py_config()` will force the initialization of Python. See [py_discover_config\(\)](#) for more details.

Value

Information about the version of Python in use, as an R list with class "py_config".

py_del_attr	<i>Delete an attribute of a Python object</i>
-------------	---

Description

Delete an attribute of a Python object

Usage

```
py_del_attr(x, name)
```

Arguments

x	A Python object.
name	The attribute name.

py_del_item	<i>Delete / remove an item from a Python object</i>
-------------	---

Description

Delete an item associated with a Python object, as through its `__delitem__` method.

Usage

```
py_del_item(x, name)
```

Arguments

x	A Python object.
name	The item name.

Value

The (mutated) object x, invisibly.

See Also

Other item-related APIs: [py_get_item\(\)](#), [py_set_item\(\)](#)

py_discover_config *Discover the version of Python to use with reticulate.*

Description

This function enables callers to check which versions of Python will be discovered on a system as well as which one will be chosen for use with reticulate.

Usage

```
py_discover_config(required_module = NULL, use_environment = NULL)
```

Arguments

`required_module`
A optional module name that must be available in order for a version of Python to be used.

`use_environment`
An optional virtual/conda environment name to prefer in the search.

Value

Python configuration object.

py_ellipsis *The builtin constant Ellipsis*

Description

The builtin constant Ellipsis

Usage

```
py_ellipsis()
```

`py_eval`*Evaluate a Python Expression*

Description

Evaluate a single Python expression, in a way analogous to the Python `eval()` built-in function.

Usage

```
py_eval(code, convert = TRUE)
```

Arguments

<code>code</code>	A single Python expression.
<code>convert</code>	Boolean; automatically convert Python objects to R?

Value

The result produced by evaluating `code`, converted to an R object when `convert` is set to `TRUE`.

Caveats

`py_eval()` only supports evaluation of 'simple' Python expressions. Other expressions (e.g. assignments) will fail; e.g.

```
> py_eval("x = 1")
Error in py_eval_impl(code, convert) :
  SyntaxError: invalid syntax (reticulate_eval, line 1)
```

and this mirrors what one would see in a regular Python interpreter:

```
>>> eval("x = 1")
Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
  File "<string>", line 1
x = 1
^
SyntaxError: invalid syntax
```

The `py_run_string()` method can be used if the evaluation of arbitrary Python code is required.

 py_exe

Python executable

Description

Get the path to the Python executable that `reticulate` has been configured to use. If Python has already been initialized, then `reticulate` will choose the currently-active copy of Python.

Usage

```
py_exe()
```

Details

This can occasionally be useful if you'd like to interact with Python (or its modules) via a subprocess; for example you might choose to install a package with `pip`:

```
system2(py_exe(), c("-m", "pip", "install", "numpy"))
```

and so you can also have greater control over how these modules are invoked.

Value

The path to the Python executable `reticulate` has been configured to use.

 py_func

Wrap an R function in a Python function with the same signature.

Description

This function could wrap an R function in a Python function with the same signature. Note that the signature of the R function must not contain esoteric Python-incompatible constructs.

Usage

```
py_func(f)
```

Arguments

`f` An R function

Value

A Python function that calls the R function `f` with the same signature.

 py_function_custom_scaffold

Custom Scaffolding of R Wrappers for Python Functions

Description

This function can be used to generate R wrapper for a specified Python function while allowing to inject custom code for critical parts of the wrapper generation, such as process the any part of the docs obtained from `py_function_docs()` and append additional roxygen fields. The result from execution of `python_function` is assigned to a variable called `python_function_result` that can also be processed by `postprocess_fn` before writing the closing curly braces for the generated wrapper function.

Usage

```
py_function_custom_scaffold(
  python_function,
  r_function = NULL,
  additional_roxygen_fields = NULL,
  process_docs_fn = function(docs) docs,
  process_param_fn = function(param, docs) param,
  process_param_doc_fn = function(param_doc, docs) param_doc,
  postprocess_fn = function() { },
  file_name = NULL
)
```

Arguments

<code>python_function</code>	Fully qualified name of Python function or class constructor (e.g. <code>tf\$layers\$average_pooling1d</code>)
<code>r_function</code>	Name of R function to generate (defaults to name of Python function if not specified)
<code>additional_roxygen_fields</code>	A list of additional roxygen fields to write to the roxygen docs, e.g. <code>list(export = "", rdname = "generated-wrappers")</code> .
<code>process_docs_fn</code>	A function to process docs obtained from <code>reticulate::py_function_docs(python_function)</code> .
<code>process_param_fn</code>	A function to process each parameter needed for <code>python_function</code> before executing <code>python_function</code> .
<code>process_param_doc_fn</code>	A function to process the roxygen docstring for each parameter.
<code>postprocess_fn</code>	A function to inject any custom code in the form of a string before writing the closing curly braces for the generated wrapper function.
<code>file_name</code>	The file name to write the generated wrapper function to. If <code>NULL</code> , the generated wrapper will only be printed out in the console.

Examples

```
## Not run:

library(tensorflow)
library(stringr)

# Example of a `process_param_fn` to cast parameters with default values
# that contains "L" to integers
process_int_param_fn <- function(param, docs) {
  # Extract the list of parameters that have integer values as default
  int_params <- gsub(
    " = [-]?[0-9]+L",
    "",
    str_extract_all(docs$signature, "[A-z]+ = [-]?[0-9]+L")[[1]])
  # Explicitly cast parameter in the list obtained above to integer
  if (param %in% int_params) {
    param <- paste0("as.integer(", param, ")")
  }
  param
}

# Note that since the default value of parameter `k` is `1L`. It is wrapped
# by `as.integer()` to ensure it's casted to integer before sending it to `tf$nn$top_k`
# for execution. We then print out the python function result.
py_function_custom_scaffold(
  "tf$nn$top_k",
  r_function = "top_k",
  process_param_fn = process_int_param_fn,
  postprocess_fn = function() { "print(python_function_result)" })

## End(Not run)
```

`py_get_attr`*Get an attribute of a Python object*

Description

Get an attribute of a Python object

Usage`py_get_attr(x, name, silent = FALSE)`**Arguments**

<code>x</code>	Python object
<code>name</code>	Attribute name
<code>silent</code>	TRUE to return NULL if the attribute doesn't exist (default is FALSE which will raise an error)

Value

Attribute of Python object

py_get_item	<i>Get an item from a Python object</i>
-------------	---

Description

Retrieve an item from a Python object, similar to how `x[name]` might be used in Python code to access an item indexed by key on an object `x`. The object's `__getitem__` method will be called.

Usage

```
py_get_item(x, key, silent = FALSE)
```

Arguments

<code>x</code>	A Python object.
<code>key</code>	The key used for item lookup.
<code>silent</code>	Boolean; when TRUE, attempts to access missing items will return NULL rather than throw an error.

See Also

Other item-related APIs: [py_del_item\(\)](#), [py_set_item\(\)](#)

py_has_attr	<i>Check if a Python object has an attribute</i>
-------------	--

Description

Check whether a Python object `x` has an attribute name.

Usage

```
py_has_attr(x, name)
```

Arguments

<code>x</code>	A python object.
<code>name</code>	The attribute to be accessed.

Value

TRUE if the object has the attribute name, and FALSE otherwise.

py_help

Documentation for Python Objects

Description

Documentation for Python Objects

Usage

py_help(object)

Arguments

object Object to print documentation for

py_id

Unique identifier for Python object

Description

Get a globally unique identifier for a Python object.

Usage

py_id(object)

Arguments

object Python object

Value

Unique identifier (as integer) or NULL

Note

In the current implementation of CPython this is the memory address of the object.

py_install

*Install Python packages***Description**

Install Python packages into a virtual environment or Conda environment.

Usage

```
py_install(
  packages,
  envname = NULL,
  method = c("auto", "virtualenv", "conda"),
  conda = "auto",
  python_version = NULL,
  pip = FALSE,
  ...,
  pip_ignore_installed = ignore_installed,
  ignore_installed = FALSE
)
```

Arguments

packages	A vector of Python packages to install.
envname	The name, or full path, of the environment in which Python packages are to be installed. When NULL (the default), the active environment as set by the RETICULATE_PYTHON_ENV variable will be used; if that is unset, then the <code>r-reticulate</code> environment will be used.
method	Installation method. By default, "auto" automatically finds a method that will work in the local environment. Change the default to force a specific installation method. Note that the "virtualenv" method is not available on Windows.
conda	The path to a conda executable. Use "auto" to allow <code>reticulate</code> to automatically find an appropriate conda binary. See Finding Conda and conda_binary() for more details.
python_version	The requested Python version. Ignored when attempting to install with a Python virtual environment.
pip	Boolean; use pip for package installation? This is only relevant when Conda environments are used, as otherwise packages will be installed from the Conda repositories.
...	Additional arguments passed to conda_install() or virtualenv_install() .
pip_ignore_installed, ignore_installed	Boolean; whether pip should ignore previously installed versions of the requested packages. Setting this to TRUE causes pip to install the latest versions of all dependencies into the requested environment. This ensure that no dependencies are satisfied by a package that exists either in the site library or was previously installed from a different—potentially incompatible—distribution channel.

(ignore_installed is an alias for pip_ignore_installed, pip_ignore_installed takes precedence).

Details

On Linux and OS X the "virtualenv" method will be used by default ("conda" will be used if virtualenv isn't available). On Windows, the "conda" method is always used.

See Also

[conda_install\(\)](#), for installing packages into conda environments. [virtualenv_install\(\)](#), for installing packages into virtual environments.

py_is_null_xptr	<i>Check if a Python object is a null externalptr</i>
-----------------	---

Description

Check if a Python object is a null externalptr

Usage

```
py_is_null_xptr(x)
py_validate_xptr(x)
```

Arguments

x	Python object
---	---------------

Details

When Python objects are serialized within a persisted R environment (e.g. .RData file) they are deserialized into null externalptr objects (since the Python session they were originally connected to no longer exists). This function allows you to safely check whether a Python object is a null externalptr.

The py_validate function is a convenience function which calls py_is_null_xptr and throws an error in the case that the xptr is NULL.

Value

Logical indicating whether the object is a null externalptr

`py_iterator`*Create a Python iterator from an R function*

Description

Create a Python iterator from an R function

Usage

```
py_iterator(fn, completed = NULL)
```

Arguments

<code>fn</code>	R function with no arguments.
<code>completed</code>	Special sentinel return value which indicates that iteration is complete (defaults to NULL)

Details

Python generators are functions that implement the Python iterator protocol. In Python, values are returned using the `yield` keyword. In R, values are simply returned from the function.

In Python, the `yield` keyword enables successive iterations to use the state of previous iterations. In R, this can be done by returning a function that mutates its enclosing environment via the `<<-` operator. For example:

```
sequence_generator <- function(start) {  
  value <- start  
  function() {  
    value <<- value + 1  
    value  
  }  
}
```

Then create an iterator using `py_iterator()`:

```
g <- py_iterator(sequence_generator(10))
```

Value

Python iterator which calls the R function for each iteration.

Ending Iteration

In Python, returning from a function without calling `yield` indicates the end of the iteration. In R however, `return` is used to yield values, so the end of iteration is indicated by a special return value (NULL by default, however this can be changed using the `completed` parameter). For example:

```

sequence_generator <-function(start) {
  value <- start
  function() {
    value <<- value + 1
    if (value < 100)
      value
    else
      NULL
  }
}

```

Threading

Some Python APIs use generators to parallelize operations by calling the generator on a background thread and then consuming its results on the foreground thread. The `py_iterator()` function creates threadsafe iterators by ensuring that the R function is always called on the main thread (to be compatible with R's single-threaded runtime) even if the generator is run on a background thread.

<code>py_last_error</code>	<i>Get or clear the last Python error encountered</i>
----------------------------	---

Description

Get or clear the last Python error encountered

Usage

```

py_last_error()

py_clear_last_error()

```

Value

For `py_last_error()`, a list with the type, value, and traceback for the last Python error encountered (can be NULL if no error has yet been encountered).

<code>py_len</code>	<i>Length of Python object</i>
---------------------	--------------------------------

Description

Get the length of a Python object. This is equivalent to calling the Python builtin `len()` function on the object.

Usage

```

py_len(x, default = NULL)

```

Arguments

x	A Python object.
default	The default length value to return, in the case that the associated Python object has no <code>__len__</code> method. When NULL (the default), an error is emitted instead.

Details

Not all Python objects have a defined length. For objects without a defined length, calling `py_len()` will throw an error. If you'd like to instead infer a default length in such cases, you can set the default argument to e.g. `1L`, to treat Python objects without a `__len__` method as having length one.

Value

The length of the object, as a numeric value.

`py_list_attributes` *List all attributes of a Python object*

Description

List all attributes of a Python object

Usage

```
py_list_attributes(x)
```

Arguments

x	Python object
---	---------------

Value

Character vector of attributes

py_list_packages *List installed Python packages*

Description

List the Python packages that are installed in the requested Python environment.

Usage

```
py_list_packages(
  envname = NULL,
  type = c("auto", "virtualenv", "conda"),
  python = NULL
)
```

Arguments

envname	The name of, or path to, a Python virtual environment. Ignored when python is non-NULL.
type	The virtual environment type. Useful if you have both virtual environments and Conda environments of the same name on your system, and you need to disambiguate them.
python	The path to a Python executable.

Details

When envname is NULL, reticulate will use the "default" version of Python, as reported by [py_exe\(\)](#). This implies that you can call `py_list_packages()` without arguments in order to list the installed Python packages in the version of Python currently used by reticulate.

Value

An R data.frame, with columns:

package The package name.

version The package version.

requirement The package requirement.

channel (Conda only) The channel associated with this package.

py_main_thread_func *Create a Python function that will always be called on the main thread*

Description

This function is helpful when you need to provide a callback to a Python library which may invoke the callback on a background thread. As R functions must run on the main thread, wrapping the R function with `py_main_thread_func()` will ensure that R code is only executed on the main thread.

Usage

```
py_main_thread_func(f)
```

Arguments

f An R function with arbitrary arguments

Value

A Python function that delegates to the passed R function, which is guaranteed to always be called on the main thread.

py_module_available *Check if a Python module is available on this system.*

Description

Note that this function will also attempt to initialize Python before checking if the requested module is available.

Usage

```
py_module_available(module)
```

Arguments

module The name of the module.

Value

TRUE if the module is available and can be loaded; FALSE otherwise.

py_none	<i>The Python None object</i>
---------	-------------------------------

Description

Get a reference to the Python None object.

Usage

```
py_none()
```

py_run	<i>Run Python code</i>
--------	------------------------

Description

Execute code within the scope of the `__main__` Python module.

Usage

```
py_run_string(code, local = FALSE, convert = TRUE)
```

```
py_run_file(file, local = FALSE, convert = TRUE)
```

Arguments

code	The Python code to be executed.
local	Boolean; should Python objects be created as part of a local / private dictionary? If FALSE, objects will be created within the scope of the Python main module.
convert	Boolean; should Python objects be automatically converted to their R equivalent? If set to FALSE, you can still manually convert Python objects to R via the py_to_r() function.
file	The Python script to be executed.

Value

A Python dictionary of objects. When `local` is FALSE, this dictionary captures the state of the Python main module after running the provided code. Otherwise, only the variables defined and used are captured.

py_save_object *Save and Load Python Objects*

Description

Save and load Python objects.

Usage

```
py_save_object(object, filename, pickle = "pickle", ...)
```

```
py_load_object(filename, pickle = "pickle", ...)
```

Arguments

object	A Python object.
filename	The output file name. Note that the file extension <code>.pickle</code> is considered the "standard" extension for serialized Python objects as created by the <code>pickle</code> module.
pickle	The "pickle" implementation to use. Defaults to "pickle", but other compatible Python "pickle" implementations (e.g. "cPickle") could be used as well.
...	Optional arguments, to be passed to the <code>pickle</code> module's <code>dump()</code> and <code>load()</code> functions.

Details

Python objects are serialized using the `pickle` module – see <https://docs.python.org/3/library/pickle.html> for more details.

py_set_attr *Set an attribute of a Python object*

Description

Set an attribute of a Python object

Usage

```
py_set_attr(x, name, value)
```

Arguments

x	Python object
name	Attribute name
value	Attribute value

`py_set_item` *Set an item for a Python object*

Description

Set an item on a Python object, similar to how `x[name] = value` might be used in Python code to set an item called `name` with value `value` on object `x`. The object's `__setitem__` method will be called.

Usage

```
py_set_item(x, name, value)
```

Arguments

<code>x</code>	A Python object.
<code>name</code>	The item name.
<code>value</code>	The item value.

Value

The (mutated) object `x`, invisibly.

See Also

Other item-related APIs: [py_del_item\(\)](#), [py_get_item\(\)](#)

`py_set_seed` *Set Python and NumPy random seeds*

Description

Set various random seeds required to ensure reproducible results. The provided seed value will establish a new random seed for Python and NumPy, and will also (by default) disable hash randomization.

Usage

```
py_set_seed(seed, disable_hash_randomization = TRUE)
```

Arguments

<code>seed</code>	A single value, interpreted as an integer
<code>disable_hash_randomization</code>	Disable hash randomization, which is another common source of variable results. See https://docs.python.org/3.4/using/cmdline.html#envvar-PYTHONHASHSEED

Details

This function does not set the R random seed, for that you should call [set.seed\(\)](#).

py_str *An S3 method for getting the string representation of a Python object*

Description

An S3 method for getting the string representation of a Python object

Usage

```
py_str(object, ...)
```

Arguments

object	Python object
...	Unused

Details

The default implementation will call PyObject_Str on the object.

Value

Character vector

py_suppress_warnings *Suppress Python warnings for an expression*

Description

Suppress Python warnings for an expression

Usage

```
py_suppress_warnings(expr)
```

Arguments

expr	Expression to suppress warnings for
------	-------------------------------------

Value

Result of evaluating expression

py_unicode	<i>Convert to Python Unicode Object</i>
------------	---

Description

Convert to Python Unicode Object

Usage

```
py_unicode(str)
```

Arguments

str	Single element character vector to convert
-----	--

Details

By default R character vectors are converted to Python strings. In Python 3 these values are unicode objects however in Python 2 they are 8-bit string objects. This function enables you to obtain a Python unicode object from an R character vector when running under Python 2 (under Python 3 a standard Python string object is returned).

py_version	<i>Python version</i>
------------	-----------------------

Description

Get the version of Python currently being used by reticulate.

Usage

```
py_version()
```

Value

The version of Python currently used, or NULL if Python has not yet been initialized by reticulate.

r-py-conversion	<i>Convert between Python and R objects</i>
-----------------	---

Description

Convert between Python and R objects

Usage

```
r_to_py(x, convert = FALSE)
```

```
py_to_r(x)
```

Arguments

x	A Python object.
convert	Boolean; should Python objects be automatically converted to their R equivalent? If set to FALSE, you can still manually convert Python objects to R via the py_to_r() function.

Value

An R object, as converted from the Python object.

repl_python	<i>Run a Python REPL</i>
-------------	--------------------------

Description

This function provides a Python REPL in the R session, which can be used to interactively run Python code. All code executed within the REPL is run within the Python main module, and any generated Python objects will persist in the Python session after the REPL is detached.

Usage

```
repl_python(
  module = NULL,
  quiet = getOption("reticulate.repl.quiet", default = FALSE),
  input = NULL
)
```

Arguments

module	An (optional) Python module to be imported before the REPL is launched.
quiet	Boolean; print a startup banner when launching the REPL? If TRUE, the banner will be suppressed.
input	Python code to be run within the REPL. Setting this can be useful if you'd like to drive the Python REPL programmatically.

Details

When working with R and Python scripts interactively, one can activate the Python REPL with `repl_python()`, run Python code, and later run `exit` to return to the R console.

Magics

A handful of magics are supported in `repl_python()`:

Lines prefixed with `!` are executed as system commands:

- `!cmd --arg1 --arg2`: Execute arbitrary system commands

Magics start with a `%` prefix. Supported magics include:

- `%conda ...` executes a conda command in the active conda environment
- `%pip ...` executes pip for the active python.
- `%load, %loadpy, %run` executes a python file.
- `%system, !!` executes a system command and capture output
- `%env`: read current environment variables.
 - `%env name`: read environment variable 'name'.
 - `%env name=val, %env name val`: set environment variable 'name' to 'val'. `val` elements in `{}` are interpolated using f-strings (required Python ≥ 3.6).
- `%cd <dir>` change working directory.
 - `%cd -`: change to previous working directory (as set by `%cd`).
 - `%cd -3`: change to 3rd most recent working directory (as set by `%cd`).
 - `%cd -foo/bar`: change to most recent working directory matching "foo/bar" regex (in history of directories set via `%cd`).
- `%pwd`: print current working directory.
- `%dhist`: print working directory history.

Additionally, the output of system commands can be captured in a variable, e.g.:

- `x = !ls`

where `x` will be a list of strings, consisting of stdout output split in `"\n"` (stderr is not captured).

Example

```
# enter the Python REPL, create a dictionary, and exit
repl_python()
dictionary = {'alpha': 1, 'beta': 2}
exit

# access the created dictionary from R
py$dictionary
# $alpha
# [1] 1
#
# $beta
# [1] 2
```

See Also

[py](#), for accessing objects created using the Python REPL.

source_python

Read and evaluate a Python script

Description

Evaluate a Python script within the Python main module, then make all public (non-module) objects within the main Python module available within the specified R environment.

Usage

```
source_python(file, envir = parent.frame(), convert = TRUE)
```

Arguments

file	The Python script to be executed.
envir	The environment to assign Python objects into (for example, <code>parent.frame()</code> or <code>globalenv()</code>). Specify <code>NULL</code> to not assign Python objects.
convert	Boolean; should Python objects be automatically converted to their R equivalent? If set to <code>FALSE</code> , you can still manually convert Python objects to R via the py_to_r() function.

Details

To prevent assignment of objects into R, pass `NULL` for the `envir` parameter.

tuple	<i>Create Python tuple</i>
-------	----------------------------

Description

Create a Python tuple object

Usage

```
tuple(..., convert = FALSE)
```

Arguments

...	Values for tuple (or a single list to be converted to a tuple).
convert	TRUE to automatically convert Python objects to their R equivalent. If you pass FALSE you can do manual conversion using the py_to_r() function.

Value

A Python tuple

Note

The returned tuple will not automatically convert its elements from Python to R. You can do manual conversion with the [py_to_r\(\)](#) function or pass `convert = TRUE` to request automatic conversion.

use_python	<i>Use Python</i>
------------	-------------------

Description

Select the version of Python to be used by reticulate.

Usage

```
use_python(python, required = NULL)
```

```
use_python_version(version, required = NULL)
```

```
use_virtualenv(virtualenv = NULL, required = NULL)
```

```
use_condaenv(condaenv = NULL, conda = "auto", required = NULL)
```

```
use_miniconda(condaenv = NULL, required = NULL)
```

Arguments

python	The path to a Python binary.
required	Is the requested copy of Python required? If TRUE, an error will be emitted if the requested copy of Python does not exist. Otherwise, the request is taken as a hint only, and scanning for other versions will still proceed.
version	The version of Python to use. <code>reticulate</code> will search for versions of Python as installed by the <code>install_python()</code> helper function.
virtualenv	Either the name of, or the path to, a Python virtual environment.
condaenv	The name of the Conda environment to use.
conda	The path to a conda executable. By default, <code>reticulate</code> will check the PATH, as well as other standard locations for Anaconda installations.

Details

The `reticulate` package initializes its Python bindings lazily – that is, it does not initialize its Python bindings until an API that explicitly requires Python to be loaded is called. This allows users and package authors to request particular versions of Python by calling `use_python()` or one of the other helper functions documented in this help file.

RETICULATE_PYTHON

The `RETICULATE_PYTHON` environment variable can also be used to control which copy of Python `reticulate` chooses to bind to. It should be set to the path to a Python interpreter, and that interpreter can either be:

- A standalone system interpreter,
- Part of a virtual environment,
- Part of a Conda environment.

When set, this will override any other requests to use a particular copy of Python. Setting this in `~/.Renviro`n (or optionally, a project `.Renviro`n) can be a useful way of forcing `reticulate` to use a particular version of Python.

Caveats

Note that the requests for a particular version of Python via `use_python()` and friends only persist for the active session; they must be re-run in each new R session as appropriate.

If `use_python()` (or one of the other `use_*` functions) are called multiple times, the most recently-requested version of Python will be used. Note that any request to `use_python()` will always be overridden by the `RETICULATE_PYTHON` environment variable, if set.

The `py_config()` function will also provide a short note describing why `reticulate` chose to select the version of Python that was ultimately activated.

Description

R functions for managing Python **virtual environments**.

Usage

```
virtualenv_create(  
  envname = NULL,  
  python = NULL,  
  ...,  
  version = NULL,  
  packages = "numpy",  
  module = getOption("reticulate.virtualenv.module"),  
  system_site_packages = getOption("reticulate.virtualenv.system_site_packages",  
    default = FALSE),  
  pip_version = getOption("reticulate.virtualenv.pip_version", default = NULL),  
  setuptools_version = getOption("reticulate.virtualenv.setuptools_version", default =  
    NULL),  
  extra = getOption("reticulate.virtualenv.extra", default = NULL)  
)  
  
virtualenv_install(  
  envname = NULL,  
  packages,  
  ignore_installed = FALSE,  
  pip_options = character(),  
  ...  
)  
  
virtualenv_remove(envname = NULL, packages = NULL, confirm = interactive())  
  
virtualenv_list()  
  
virtualenv_root()  
  
virtualenv_python(envname = NULL)  
  
virtualenv_exists(envname = NULL)
```

Arguments

envname	The name of, or path to, a Python virtual environment. If this name contains any slashes, the name will be interpreted as a path; if the name does not contain slashes, it will be treated as a virtual environment within <code>virtualenv_root()</code> .
---------	---

	When NULL, the virtual environment as specified by the <code>RETICULATE_PYTHON_ENV</code> environment variable will be used instead. To refer to a virtual environment in the current working directory, you can prefix the path with <code>./<name></code> .
<code>python</code>	The path to a Python interpreter, to be used with the created virtual environment. When NULL, the Python interpreter associated with the current session will be used.
<code>...</code>	Optional arguments; currently ignored and reserved for future expansion.
<code>version</code>	The version of Python to be used with the newly-created virtual environment. Python installations as installed via <code>install_python()</code> will be used.
<code>packages</code>	A set of Python packages to install (via <code>pip install</code>) into the virtual environment, after it has been created. By default, the "numpy" package will be installed, and the <code>pip</code> , <code>setuptools</code> and <code>wheel</code> packages will be updated. Set this to <code>FALSE</code> to avoid installing any packages after the virtual environment has been created.
<code>module</code>	The Python module to be used when creating the virtual environment – typically, <code>virtualenv</code> or <code>venv</code> . When NULL (the default), <code>venv</code> will be used if available with Python <code>>= 3.6</code> ; otherwise, the <code>virtualenv</code> module will be used.
<code>system_site_packages</code>	Boolean; create new virtual environments with the <code>--system-site-packages</code> flag, thereby allowing those virtual environments to access the system's site packages? Defaults to <code>FALSE</code> .
<code>pip_version</code>	The version of <code>pip</code> to be installed in the virtual environment. Relevant only when <code>module == "virtualenv"</code> . Set this to <code>FALSE</code> to disable installation of <code>pip</code> altogether.
<code>setuptools_version</code>	The version of <code>setuptools</code> to be installed in the virtual environment. Relevant only when <code>module == "virtualenv"</code> . Set this to <code>FALSE</code> to disable installation of <code>setuptools</code> altogether.
<code>extra</code>	An optional set of extra command line arguments to be passed. Arguments should be quoted via <code>shQuote()</code> when necessary.
<code>ignore_installed</code>	Boolean; ignore previously-installed versions of the requested packages? (This should normally be <code>TRUE</code> , so that pre-installed packages available in the site libraries are ignored and hence packages are installed into the virtual environment.)
<code>pip_options</code>	An optional character vector of additional command line arguments to be passed to <code>pip</code> .
<code>confirm</code>	Boolean; confirm before removing packages or virtual environments?

Details

Virtual environments are by default located at `~/virtualenvs` (accessed with the `virtualenv_root()` function). You can change the default location by defining the `WORKON_HOME` environment variable.

```
with.python.builtin.object
```

Evaluate an expression within a context.

Description

The with method for objects of type python.builtin.object implements the context manager protocol used by the Python with statement. The passed object must implement the **context manager** (`__enter__` and `__exit__` methods).

Usage

```
## S3 method for class 'python.builtin.object'  
with(data, expr, as = NULL, ...)
```

Arguments

data	Context to enter and exit
expr	Expression to evaluate within the context
as	Name of variable to assign context to for the duration of the expression's evaluation (optional).
...	Unused

Index

- * **datasets**
 - py, [15](#)
- * **item-related APIs**
 - py_del_item, [19](#)
 - py_get_item, [25](#)
 - py_set_item, [36](#)
- * **miniconda-tools**
 - install_miniconda, [11](#)
 - miniconda_uninstall, [14](#)
 - miniconda_update, [14](#)
- * **miniconda**
 - miniconda_path, [14](#)

array_reshape, [3](#)
as.character.python.builtin.bytes, [4](#)
as_iterator(iterate), [13](#)

conda-tools, [5](#)
conda_binary(conda-tools), [5](#)
conda_binary(), [6](#), [27](#)
conda_clone(conda-tools), [5](#)
conda_create(conda-tools), [5](#)
conda_exe(conda-tools), [5](#)
conda_export(conda-tools), [5](#)
conda_export(), [6](#)
conda_install(conda-tools), [5](#)
conda_install(), [27](#), [28](#)
conda_list(conda-tools), [5](#)
conda_python(conda-tools), [5](#)
conda_remove(conda-tools), [5](#)
conda_update(conda-tools), [5](#)
conda_version(conda-tools), [5](#)
configure_environment, [7](#)

dict, [8](#)

eng_python, [9](#)

import, [10](#)
import_builtins(import), [10](#)
import_from_path(import), [10](#)

import_main(import), [10](#)
install_miniconda, [11](#), [14](#), [15](#)
install_python, [12](#)
install_python(), [12](#), [13](#), [43](#), [45](#)
iter_next(iterate), [13](#)
iterate, [13](#)

miniconda_path, [12](#), [14](#), [15](#)
miniconda_path(), [7](#)
miniconda_uninstall, [12](#), [14](#), [15](#)
miniconda_update, [12](#), [14](#), [14](#)

np_array, [15](#)

py, [15](#), [41](#)
py_available, [16](#)
py_bool, [17](#)
py_capture_output, [18](#)
py_clear_last_error(py_last_error), [30](#)
py_config, [18](#)
py_config(), [43](#)
py_del_attr, [19](#)
py_del_item, [19](#), [25](#), [36](#)
py_dict(dict), [8](#)
py_discover_config, [20](#)
py_discover_config(), [18](#)
py_ellipsis, [20](#)
py_eval, [21](#)
py_exe, [22](#)
py_exe(), [32](#)
py_func, [22](#)
py_function_custom_scaffold, [23](#)
py_function_docs(), [23](#)
py_get_attr, [24](#)
py_get_attr(), [10](#)
py_get_item, [19](#), [25](#), [36](#)
py_has_attr, [25](#)
py_help, [26](#)
py_id, [26](#)
py_install, [27](#)

`py_is_null_xptr`, 28
`py_iterator`, 29
`py_last_error`, 30
`py_len`, 30
`py_list_attributes`, 31
`py_list_packages`, 32
`py_load_object (py_save_object)`, 35
`py_main_thread_func`, 33
`py_module_available`, 33
`py_none`, 34
`py_numpy_available (py_available)`, 16
`py_run`, 34
`py_run_file (py_run)`, 34
`py_run_string (py_run)`, 34
`py_run_string()`, 21
`py_save_object`, 35
`py_set_attr`, 35
`py_set_item`, 19, 25, 36
`py_set_seed`, 36
`py_str`, 37
`py_suppress_warnings`, 37
`py_to_r (r-py-conversion)`, 39
`py_to_r()`, 8–10, 34, 39, 41, 42
`py_unicode`, 38
`py_validate_xptr (py_is_null_xptr)`, 28
`py_version`, 38
`PyClass`, 16

`r-py-conversion`, 39
`r_to_py (r-py-conversion)`, 39
`repl_python`, 39

`set.seed()`, 37
`source_python`, 41

`tuple`, 42

`use_condaenv (use_python)`, 42
`use_miniconda (use_python)`, 42
`use_python`, 42
`use_python_version (use_python)`, 42
`use_virtualenv (use_python)`, 42

`virtualenv-tools`, 44
`virtualenv_create (virtualenv-tools)`, 44
`virtualenv_exists (virtualenv-tools)`, 44
`virtualenv_install (virtualenv-tools)`,
44
`virtualenv_install()`, 27, 28
`virtualenv_list (virtualenv-tools)`, 44
`virtualenv_python (virtualenv-tools)`, 44
`virtualenv_remove (virtualenv-tools)`, 44
`virtualenv_root (virtualenv-tools)`, 44
`with.python.builtin.object`, 46